Ehoma
Clamping Solutions By ITM

HIGH FORCE FORGED STEEL CLAMP

Larger rail sizes & shorter depths giving high clamping force. Knurled clamping face & pad provide stronger grip on the workpiece.



Socket drive handle featured on clamps with 30mm or 40mm rail size



Knurled pads




Part No.	Span x Depth	Rail Size	Clamping Force
EC-SP20C8	200 x 80mm	27 x 13mm	1100kg
EC-SP25C8	250 x 80mm	27 x 13mm	1100kg
EC-SP30C8	300 x 80mm	27 x 13mm	1100kg
EC-SP25C10	250 x 100mm	30 x 15mm	1400kg
EC-SP40C10	400 x 100mm	30 x 15mm	1400kg
EC-SP60C10	600 x 100mm	30 x 15mm	1400kg
EC-SP30C12	300 x 120mm	40 x 20mm	2600kg
EC-SP50C12	500 x 120mm	40 x 20mm	2600kg
EC-SP100C12	1000 x 120mm	40 x 20mm	2600kg

QUICK ACTION LEVER FORGED STEEL CLAMP

Ratchet type lever prevents overloading & resists vibration. For high pressure, fast action clamping purposes.



Fast & easy to use






Part No.	Span x Depth	Rail Size	Clamping Force
EC-G16L	160 x 80mm	16 x 7.5mm	300kg
EC-G20L	200 x 100mm	19.5 x 9.5mm	350kg
EC-G30L	300 x 140mm	25 x 12mm	500kg
EC-G40L	400 x 120mm	25 x 12mm	550kg
EC-G50L	500 x 120mm	25 x 12mm	550kg

PIVOT HANDLE FORGED STEEL CLAMP

The comfortable pivot handle makes it easier to achieve maximum clamping pressure & allows faster clamping in restricted working areas



Easy operation in restricted working areas





Part No.	Span x Depth	Rail Size	Clamping Force
EC-REG20C	200 x 100mm	19.5 x 9.5mm	450kg
EC-REG30C	300 x 140mm	25 x 12mm	670kg
EC-REG40C	400 x 175mm	27 x 13mm	700kg
EC-REG60C	600 x 175mm	27 x 13mm	700kg

BEAM FORGED STEEL CLAMP


- U-Turn design is ideal for clamping
- H beam when welding



Changeable heads



Socket drive handle





Part No.	Span x Depth (A x B)	U Depth (C)	Overpass (D)	Rail Size	Clamping Force
EC-H25U6	250 x 120mm	60	90	22 x 10.5mm	550kg
EC-H30U10	300 x 140mm	100	100	25 x 12mm	650kg
EC-H30U11	300 x 140mm	110	115	30 x 15mm	1100kg
EC-H50U11	500 x 140mm	110	115	30 x 15mm	1100kg
EC-H30U15	300 x 175mm	150	130	40 x 20mm	2200kg
EC-H40U15	400 x 175mm	150	130	40 x 20mm	2200kg
EC-H50U15	500 x 175mm	150	130	40 x 20mm	2200kg