NORTON

MOUNTED POINTS FOR DIE GRINDERS

Applications for A-shaped mounted points include

- Foundry work - finishing castings
- Deburring cut metal
- Tool, die and precision engineering work

W-shaped mounted points are primarily used for

- Internal diameter (I.D.) grinding
- Jig grinding of bores and deep recesses
- Weld seam blending
- All mounted points below have a spindle dimension of 6.35 x 40mm



BETTER ++++

METAL INOX

SHAPE	DIM (mm)	GRIT	COLOUR	BOND	RPM	PART NUMBER	BARCODE	MOQ
A1	20 x 65	60	White Aluminium Oxide	Vitrified	19800	61463624375	9310357703532	10
A3	25 x 70	60	White Aluminium Oxide	Vitrified	16100	61463624378	9310357704072	10
A5	20 x 28	60	Pink Aluminium Oxide	Vitrified	30000	66253183095	9310357703860	10
A11	22 x 45	60	White Aluminium Oxide	Vitrified	19860	61463624385	9310357703556	10
A11	22 x 45	36	Brown Aluminium Oxide	Resin	19860	66253183055	9310357253785	10
A38	25 x 25	60	Pink Aluminium Oxide	Vitrified	25000	66253183106	9310357703822	10
A39	20 x 20	60	Pink Aluminium Oxide	Vitrified	34000	66253183107	9310357703839	10
W218	25 x 13	36	Brown Aluminium Oxide	Resin	30000	61463633214	9310357290698	10
W220	25 x 25	36	Brown Aluminium Oxide	Resin	25500	66253183057	9310357253860	10
W236	40 x 13	36	Brown Aluminium Oxide	Resin	20000	66253183058	9310357253877	10
W237	40 x 25	36	Brown Aluminium Oxide	Resin	19000	66253183059	9310357253891	10
W242	50 x 25	36	Brown Aluminium Oxide	Resin	16000	66253183060	9310357253907	10

