Non-woven belts

BSGB FVV

Non-woven nylon fabric on an open textile backing with in-built grinding agent. For a metallically pure finish. For deburring, matting and finishing any stainless steel and steel components. Produces a uniform decorative finish on stainless steel and non-ferrous metals.

Other dimensions and grits on request.

C = coarse, M = medium, VF = very fine, SF = super fine, UF = ultra fine

Applications

max. 30 m/s



Width	Length	Grain size	Color	max. Speed	ID-No.	Mat.-No.	
mm	mm			min-1			
6	305	C	Brown	20 000	908 922 00	100 009 785	20
6	305	M	Red	20 000	908 358 00	100 009 321	20
6	305	VF	Blue	20 000	908 359 00	100 009 322	20
6	305	SF	Gray	20 000	908 360 00	100 009 323	20
6	520	C	Brown	16 000	900 860 00	100 011 858	20
6	520	M	Red	16 000	900 861 00	100 011 859	20
6	520	VF	Blue	16 000	900 862 00	100 011 860	20
6	520	UF	White	16 000	908 715 00	100 009 636	20
9	305	M	Red	20 000	908 361 00	100 009 324	20
9	305	VF	Blue	20 000	908 362 00	100 009 325	20
9	305	SF	Gray	20 000	908 363 00	100 009 326	20
12	520	C	Brown	16 000	900 863 00	100 011 861	20
12	520	M	Red	16 000	900 864 00	100 011 862	20
12	520	VF	Blue	16 000	900 865 00	100 011 863	20
12	520	SF	Gray	16 000	908 701 00	100 009 624	20
12	520	UF	White	16 000	908 716 00	100 009 637	20
16	520	C	Brown	16 000	900 866 00	100 011 864	20
16	520	M	Red	16 000	900 867 00	100 011 865	20
16	520	VF	Blue	16 000	900 868 00	100 011 866	20
19	520	C	Brown	16 000	900 879 00	100 011 872	20
19	520	M	Red	16 000	900 880 00	100 011 873	20
19	520	VF	Blue	16 000	900 881 00	100 011 874	20
19	520	SF	Gray	16 000	908 702 00	100 009 625	20
19	520	UF	White	16 000	908 813 00	100 009 725	20
30	533	C	Brown	9 000	908 591 00	100 009 522	5
30	533	M	Red	9 000	908 592 00	100 009 523	5
30	533	VF	Blue	9 000	908 593 00	100 009 524	5
30	533	SF	Gray	9 000	908 703 00	100 009 626	5
30	533	UF	White	9 000	908 699 00	100 009 622	5
30	610	C	Brown	9 000	909 701 00	100 008 892	5
30	610	M	Red	9 000	909 702 00	100 008 893	5
30	610	VF	Blue	9 000	909 703 00	100 008 894	5
30	610	SF	Gray	9 000	909 704 00	100 008 895	5
30	610	UF	White	9 000	909 766 00	100 008 949	5
50	450	C	Brown	5 700	907 103 00	100 010 204	5
50	450	M	Red	5 700	907 038 00	100 010 161	5
50	450	VF	Blue	5 700	903 444 00	100 011 206	5
50	450	SF	Gray	5 700	907 628 00	100 010 318	5
50	450	UF	White	5 700	907 027 00	100 010 160	5
63	950	C	Brown	3 200	907 954 00	100 010 484	5
63	950	M	Red	3 200	907 104 00	100 010 205	5
63	950	VF	Blue	3 200	903 445 00	100 011 208	5

Compressed non-woven discs

FVVS-K

Removing heat tinting, smoothing surfaces, light cleaning and deburring work. For removing pre-grinding marks on any metal.

EC = extra coarse, VC = very coarse, C = coarse, M = medium, VF = very fine, SF = super fine

Applications

max. 40 m/s



Diameter	Grain size	max. Speed	ID-No.	Mat.-No.	
mm		min-1			
115	EC	8000	913 030 00	100 007 612	10
115	VC	8000	913 060 00	100 007 640	10
115	C	8000	906 377 00	100 010 021	10
115	M	8000	906 378 00	100 010 022	10
115	VF	8000	906 379 00	100 010 023	10
115	SF	8000	906 380 00	100 010 024	10
125	C	8000	912 953 00	100 007 550	10
125	M	8000	912 915 00	100 007 517	10
125	VF	8000	912 954 00	100 007 551	10
178	C	6000	908 013 00	100 010 426	10
178	M	6000	908 014 00	100 010 427	10
178	VF	6000	908 015 00	100 010 428	10

FSS-K Z

Fits FVVS-K non-woven discs. Discs are easy to centre. For precise, low-vibration work.



Diameter	Thread	max. Speed	ID-No.	Mat.-No.	
mm		min-1			
115	M 14	10000	913 031 00	100 007 613	1
125	M 14	10000	912 955 00	100 007 552	1