


# RK353857 Molybond® Opal Hi-Load Lithium Complex Grease 450g

**Description:**

**MOLYBOND® Opal High Load** is a superior lithium complex grease containing molybdenum disulphide, designed for applications where a high-quality multi-purpose grease is required.

**Opal High Load** is provides improved lubrication for manufacturing and processing plants, earthmoving equipment and road transport and is an excellent general-purpose grease for open cut and underground mining.

**Opal High Load** is formulated to provide excellent load carrying capacity, protection against wear, and resistance to water wash-out.

**Intended Use:**

- Anti-friction bearings
- Plain bearings

**Product Features:**

- **Multi-purpose grease**
- **Excellent resistance to water washout**
- **Extremely high load carrying capacity**
- **Operating temperature range -30˚C to +180˚C**
- **Excellent anti wear properties**
- **MPI Approved C13 (All animal products except dairy)**




# RK311557 Molybond® GC10 multi-Purpose Non-Melt Clay Based Grease 450g

**Description:**

**MOLYBOND® GC10** is a multi-purpose, non-melt, clay-based grease formulated for high temperature applications.

**GC10** It is suitable for continuous operation up to 220°C and for intermittent operation at temperatures of up to 260°C. The solid lubricant particles carry the load and prevent metal to metal contact.

**GC10** grease is recommended for applications where high temperature stability is critical.

**Intended Use:**

- Ball and roller bearings
- Plain bearings

**Product Features:**

- **Multi-purpose grease**
- **Excellent resistance to shock loading**
- **High load carrying capacity**
- **Reduces friction**
- **Resists water wash-out**
- **Extends component life**
- **Wide temperature range**




# RY424031 Rocol® Sapphire Aqua 450g

**Description:**

**ROCOL® Sapphire Aqua** is a long-life, water-resistant grease designed for effective lubrication and protection of all types of plant and machinery exposed to wet conditions such as those found in the mineral processing and marine industries.

**Sapphire Aqua** is ideal for ball, roller or plain bearings exposed to either salt or fresh water.

**Intended Use:**

- Boat trailer wheel bearings
- Boat winches
- Washeries
- Slipway apparatus
- Water pumps

**Product Features:**

- **Extremely water resistant.**
- **Good anti-wear characteristics.**
- **Excellent corrosion resistance.**
- **High load carrying properties.**
- **Wide temperature range -30˚C to 180˚C.**
- **MPI Approved C11 (All animal product except dairy).**
- **MPI Approved for farm dairies & dairy processing.**




# RY424001 Rocol® Sapphire Hi-Temp Bearing Grease 400g

**Description:**

**ROCOL® Sapphire Hi-Temp (2)** is a bearing grease designed for the effective lubrication and protection of bearings operating at elevated temperatures.

**Sapphire Hi-Temp** is based on synthetic oil and therefore, unlike mineral oil-based greases will not carbonise at elevated temperatures or form abrasive carbon deposits.

**Intended Use:**

- Kiln car bearings
- Overhead conveyor bearings on powder coating lines
- Plain bearings
- Ball and roller bearings

**Product Features:**

- **Long term lubrication at elevated temperatures**
- **Synthetic base eliminates carbonising**
- **Protects against corrosion**
- **High load carrying capacity**
- **Wide operating temperature range -40°C to 200°C**
- **MPI Approved C11 (All animal products except dairy)**
- **AsureQuality assessed**
- **MPI Approved for farm dairies & dairy processing**




# RY424851 Rocol® Sapphire Ultraplex High Performance Lithium Bearing Grease 450g

**Description:**

**ROCOL® Sapphire Ultraplex** is a multifunctional, lithium complex based bearing grease suitable for use over a wide range of applications.

**Sapphire Ultraplex** can be used for complete plant lubrication on both anti-friction and plain bearings operating in harsh conditions such as high loads, wet and dusty environments.

**Intended Use:**

- Electric motor bearings
- Conveyor roller bearings
- Pump bearings
- Crushing and screening plants
- Automotive wheel bearings
- General plant greasing

**Product Features:**

- **Extends lubrication periods.**
- **Good adhesive properties.**
- **High load carrying capacity.**
- **Temperature range up to 180˚C continuous and 200˚C intermittently.**
- **MPI Approved C13 (All animal product except dairy).**
- **AsureQuality assessed.**
- **MPI Approved for farm dairies & dairy processing.**




# RY515330 Rocol® FOODLUBE® Grease 2 400g

**Description:**

**ROCOL® FOODLUBE® Grease** is a range of white, tenacious, non-toxic bearing greases designed for the effective lubrication and protection of ball, roller and plain bearings, slides and bushes operating under high loads in the food, pharmaceutical and other clean industries.

FOODLUBE® Grease is a synthetic hydrocarbon based grease thickened with aluminium complex and contains both solid lubricants and chemical EP additives for increased load carrying and anti-wear properties.

FOODLUBE® Grease offers excellent water wash off resistance and corrosion protection suitable for multi-purpose applications in conditions such as low or high temperatures, high loads and wet environments.

**Intended Use:**

- Ball and roller bearings
- Sliding surfaces
- Plain bearings

**Product Features:**

- **Versatile product suitable for a vast range of applications**
- **Available in NLGI No.2 & 00 consistencies**
- **Contains FDA listed ingredients FDA CFR 178.3570**
- **Outstanding load carrying capabilities**
- **Wide temperature range**
- **Highly resistant to water wash off**
- **Suitable for use in high-speed electric motors and fans**
- **Excellent corrosion protection**
- **Does not contain any animal derived materials, nut oils or genetically modified ingredients**
- **HACCP Australia Pty Ltd endorsed**
- **NSF H1 Registered**
- **MPI Approved C15 (All animal product except dairy)**
- **AsureQuality Assessed**
- **MPI Approved for farm dairies & dairy processing**




# RY421515 Rocol® Sapphire Silicone Grease (MX22) Tube 120g

**Description:**

**ROCOL® Sapphire Silicone (MX 22)** is a non-melting grease suitable for long term lubrication at extremes of temperature and is extremely water resistant and also resistant to a wide range of chemicals, oils and gases.

**Sapphire Silicone** can also be used as an electrical insulating and filling compound.

**Sapphire Silicone** is suitable for lubricating rubber seals and 'O' rings as it does not affect most polymeric material.

**Intended Use:**

- Rubber seals and 'O' rings
- Tapware for potable water
- Low speed bearings
- Slides and adjustment spindles

**Product Features:**

- **Extremely water resistant**
- **Excellent high temperature resistance**
- **Resistant to a variety of chemicals, oils and gases**
- **Wide temperature range -40 to +200°C, to 220°C intermittently**
- **Does not affect most rubbers and plastics**
- **MPI Approved C15 (All animal products except dairy)**
- **MPI Approved for farm dairies & dairy processing**
- **AsureQuality assessed**
- **NSF Registered H1 – 144603**
- **HACCP Australia Pty endorsed**