# HIGH TEMPERATURE WHEEL BEARING GREASE

Last updated: 29/06/2021 11:37 am

| PRODUCT CODE | PACK SIZE | CARTON QTY |
|---|---|---|
| HTGR00045 | 450g | 6 |
| HTGR0005 | 500g | 6 |
| HTGR0025 | 2.5Kg | 4 |
| HTGR020 | 20Kg | |
| HTGR180 | 180Kg | |




## PRODUCT BENEFITS

**High Temperature Wheel Bearing Grease** is an NLGI No 2, light blue coloured, high temperature all-purpose, extreme pressure (EP) grease manufactured from high quality base oils and a lithium complex soap thickener. It is formulated with state of the art grease additives that provide tackiness, excellent load carrying ability, outstanding resistance to water washout as well as effective extreme pressure performance and anti-wear protection.

## APPLICATION

**High Temperature Wheel Bearing Grease** is suitable for use in all general chassis grease applications in automotive and industrial service, including in cars, 4WDs, trucks and buses.

**High Temperature Wheel Bearing Grease** is particularly suitable for use in wheel bearings of vehicles fitted with disc brakes, as well as drum brakes, boat trailer wheel bearings and other marine applications.

**High Temperature Wheel Bearing Grease** is also a highly effective industrial grease in applications such as rolling element bearings, plain bearings, medium speed anti-friction bearings, steel mills, underground tunneling or mining and ore crushing plants, general plant lubrication and in agricultural and construction equipment.

## PRODUCT BENEFITS

- High temperature performance
- Excellent resistance to water wash out
- Protects against rust and corrosion, even in salt water
- Long service life
- Lead and chlorine free
- Good pumpability
- Contains tackifiers to help grease stay in place

## PRODUCT PERFORMANCE LEVELS

- DIN 51502: KP2N-30
- ISO 6743: ISO-L-XCDIB 2
- NLGI 2
- Volvo 97720 (level)

## TYPICAL DATA

| | |
|---|---|
| Colour | Light Blue |
| NLGI Grade | 2 |
| Soap Type | Lithium Complex |
| Density at 15°C, kg/L | 0.9 |
| Base Oil Viscosity, ISO | 220 |
| Operating Temperature Range °C | -10° to +170° |
| Appearance | Smooth / Tacky |
| Drop Point, °C | 290 |
| 4-ball Weld Load, kg | 315 |
| Maximum Temperature, Intermittent use, °C | 200 |

**PENRITE OIL COMPANY PTY LTD** ABN 25 005 001 525
110 Greens Rd, Dandenong South, Victoria 3175 Australia
Phone: 1300-PENRITE (1300 736 748)
Fax: 1800-PENRITE (1800 736 748)

**International** Ph: +61 3 9801 0877, Fax: +61 (0)3 8710 6601
**New Zealand** Ph:0800 533 698, Fax: 0508 736 748
Website: www.penriteoil.com.au
Email: penrite@penriteoil.com.au